7.0 COMPARISON OF THE OPTIONS

- 1 This section provides a summary comparison of the relative performance of the four Options in
- 2 addressing the seventeen evaluation criteria. The purpose of this section is to provide a
- 3 summary comparison of the performance of the Options relative to each other and, in some
- 4 cases, to base conditions. Details of the evaluations of the Options against the criteria are
- 5 presented in Sections 3, 4, 5, and 6 of this report and all comparative conclusions presented here
- 6 are more fully described in those previous sections. In this section, the criteria are grouped into
- 7 and presented by the categories:
- biological criteria,
- 9 planning criteria,
- flexibility/durability/sustainability criteria, and
- other resource impacts criteria.
- 12 The comparative evaluation of the Options in relation to the biological criteria is presented by
- 13 fish species as individual species (e.g., delta smelt) or groups of species (e.g., green and white
- sturgeon). The comparative evaluation of Options for the other groups of criteria is presented
- by criterion (e.g., planning criteria #8). Table 7-1 presents the comparative performance of each
- Option in addressing the needs of the covered fish species relative to the biological criteria.
- 17 Table 7-2 presents the comparison of the performance of each Option relative to the planning,
- 18 flexibility/durability/sustainability, and other resource impacts criteria. Table 7-3 presents the
- 19 overall performance of the Options against the major categories of criteria.
- Note that the summary evaluation of Option 2 presented here is expressed for Option 2 with a
- 21 pump facility at the siphon. As described in Section 2.2 and Section 4, it is unlikely that Option 2
- 22 as currently configured would be considered for development of the conservation strategy
- 23 because hydrodynamic modeling results indicate that with a gravity siphon it could not meet
- 24 water supply objectives. Consequently, the summary tables presented in this section present the
- evaluation results for Option 2 with the pump facility rather than for Option 2 as originally
- described in previous BDCP documents. Section 4 presents the criteria evaluation results for
- 27 Option 2 with and without the pump facility. Hydrodynamic model runs for Option 2 have
- 28 recently been conducted with the pump facility included, but results at the time of publication
- of this report are preliminary. Some of the new modeling outputs are used in the evaluation.
- 30 The evaluation of Option 2, therefore, is based more on best professional judgment and more
- 31 coarse estimates of outcomes than the other Options.
- 32 The comparison evaluation presented in this section is built on the discussions in Section 3, 4, 5,
- and 6 and on information presented in Appendix H. Appendix H contains more detailed scaling
- of the performance of each of the Options relative to the metrics used to evaluate each of the
- 35 covered fish species and each of the evaluation criteria. Summary comparisons provided in
- 36 Tables 7-1, 7-2, and 7-3 consolidate the more detailed information provided in this section and
- 37 Appendix H.

Table 7-1. Comparison of Options by Covered Fish Species

Smaring	Performance Rank ¹				
Species	Option 1	Option 2	Option 3	Option 4	
Delta smelt	•	••	•••	••••	
Longfin smelt	•	••	•••	••••	
Sacramento River Salmonids	•••	•••	•••	••••	
San Joaquin River Salmonids	•	••	•••	••••	
White Sturgeon	•	•••	•••	••••	
Green Sturgeon	•••	•••	•••	••••	
Sacramento splittail	••	••	•••	••••	
San Joaquin River Salmonids White Sturgeon Green Sturgeon	•	•••	•••	••••	

Notes:

- •••• = Best performing,
- ••• = Second best performing,
- •• = Third best performing,
- = Lowest performing

Where ranks are equal the two Options receive same rank

Table 7-2. Comparison of Options by Planning, Feasibility/Durability/Sustainability, and Other Resource Impacts Criteria

Criterion		Performa	nce Rank ¹	
	Option 1	Option 2	Option 3	Option 4
Planning Criteria				
8. Water supply goals	••	•	••••	•••
9. Feasibility/practicability	••••	••••	••••	••••
10. Minimize cost	•	••	•••	••••
Flexibility/Sustainability/Durability Criteria				
11. Durability to catastrophic events	•	••	••••	•••
12. Minimize ongoing resource input for long-term conservation	•	••	•••	••••
13. Flexibility/adaptability	•	••	•••	••••
14. Reversibility	••••	•••	••	••
Other Resource Impacts Criteria				
15. Avoidance of impacts on other native species (in-Delta)	••••	••	•	•••
16. Avoidance of impacts on human environment (in-Delta) ²	••••	•••	•	••
17. Avoidance of impacts on native species (outside Delta)	••	••	••••	•••

Notes:

1

- 1. Derived from information presented in Sections 7.2, 7.3, and 7.4.
- 2. Does not include indirect effects in export service areas.

Criteria performance ranks are:

- •••• = Best performing,
- ••• = Second best performing,
- •• = Third best performing,
- = Lowest performing

Where ranks are equal the two Options receive same rank

^{1.} Based on information presented in Tables H-1 to H-9 addressing Biological Criteria #1-7. Species performance ranks are:

Table 7-3. Overall Comparison of Options by Criteria Category (Rank)¹

Evaluation Criteria Category	Conservation Strategy Option			
	Option 1	Option 2	Option 3	Option 4
Biological	•	••	•••	••••
Planning	•	•	••••	••••
Flexibility/ Sustainability/Durability	•	••	•••	••••
Impacts on Other Resources	••••	•••	•	••

Notes:

- 1. Derived from information presented in Tables 7.1 and 7.2. Criteria performance ranks are:
 - •••• = Best performing,
 - ••• = Second best performing,
 - •• = Third best performing,
 - = Lowest performing

Where ranks are equal the two Options receive same rank

2 7.1 COMPARISON OF THE OPTIONS RELATIVE TO BIOLOGICAL CRITERIA

- 3 This section provides a comparison of the performance of each Option for benefiting each of the
- 4 covered fish species based on the biological criteria evaluations presented in Sections 3.1, 4.1,
- 5 5.1, and 6.1. Appendix H provides a summary description of the performance of each Option
- 6 relative to the evaluation criteria and metrics. Table 7-1 presents a comparison of the
- 7 performance of each Option for each fish species or species group. Tables 7-4 through 7-12
- 8 summarize the performance of each Option relative to important stressors for each of the
- 9 species.

1

10 **7.1.1 Delta Smelt**

- Option 4 would provide the greatest benefit to delta smelt because it ranks consistently best in
- 12 relieving highly important and moderately important stressors (Table 7-4). Option 3 would
- provide the second greatest benefit to delta smelt, followed by Option 2. Option 1 would
- 14 provide the lowest benefit to delta smelt because it consistently ranked lowest in relieving
- 15 important stressors to delta smelt. All Options, however, provide benefits for delta smelt
- 16 relative to base conditions.
- 17 Option 1 would provide the lowest benefit to delta smelt. Although Option 1 would relieve
- multiple stressors, it consistently ranks lowest in performance among the Options. Option 1 is
- 19 ranked lowest in benefits to quantity and quality of food, rearing and spawning habitat,
- 20 turbidity, predation, and CVP/SWP entrainment. Option 1 performs best among the Options in
- 21 reducing exposure of delta smelt to toxics, though this effect does not differ from base
- 22 conditions.

Table 7-4. Summary of Option Effects on Important Delta Smelt Stressors

Ct 1	Option	n Effects Relative to	Important Species	Stressors
Stressors ¹	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important S	Stressors			
Reduced food	•	••	•••	••••
Reduced 100d	3	3	3	3
Reduced rearing	•	••	•••	••••
habitat	3	3	3	3
Reduced	•	••	•••	•••
turbidity	3	3	3	3
Reduced	••	•••	•••	••••
spawning habitat	2	2	2	2
Reduced food	••	•••	•••	••••
quality	1	1	1	1
Moderately Import	ant Stressors			
Predation	••	•••	•••	••••
Tredation	1	1	1	1
CVP/SWP	8	••	•••	••••
entrainment	4	2	3	4
Exposure to	8	00	000	000
toxics	4	1	1	1

Notes:

1

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects. 2.
 - Effects (relative to base conditions):
 - = very low benefit,
 - •• = low benefit,
 - ••• = moderate benefit,
 - •••• = high,
 - ⊗ = no change,
 - o = very low adverse effect,
 - $\circ \circ = low adverse effect,$
 - 000 = moderate adverse effect.
 - $\circ \circ \circ \circ = \text{high adverse effect.}$
- Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High3 = Moderate

 - 2 = Low
 - 1 = little or no certainty.

- 2 Option 2 would provide the third highest benefit to delta smelt. Like Option 3, Option 2 would
- 3 need to maintain export water quality standards in the southern Delta, but, unlike Option 3, this
- 4 need would extend to all flow conditions in all water year types under Option 2. As a result, the
- ability to increase food quantity and accessibility and increase turbidity would be reduced
- under Option 2. Further, entrainment at CVP/SWP pumps would be greater under Option 2 6
- 7 than under Options 3 and 4.
- 8 Option 3 would provide the second highest benefit to delta smelt. A primary difference
- 9 between Option 3 and Option 4 is the need under Option 3 to meet export water quality
- 10 standards in the south Delta, and the adverse effects of increased reverse flows within Middle
- River, when the south Delta export facilities are operating, resulting in a reduced area available 11

- for potential habitat restoration. Option 3 provides the best opportunity to increase turbidity
- 2 and reduce CVP/SWP entrainment. Option 3 provides the second highest opportunity (after
- 3 Option 4) to increase delta smelt rearing and spawning habitat, increase food quantity, quality,
- 4 and accessibility, and reduce predation by non-natives.
- 5 Option 4 would perform best among the Options for delta smelt because it would provide the
- 6 best opportunity to relieve four of the five highly important stressors. This Option provides the
- 7 greatest increase in food quantity and quality by providing the largest area, with the greatest
- 8 geographic distribution, in which to restore habitat that, if appropriately designed, would
- 9 promote the growth and abundance of native prey species and reduce abundances of non-
- 10 native competitors and predators. Food quantity would also likely improve under Option 4 by
- reducing exports of nutrients and organic carbon by CVP/SWP pumps and increasing
- 12 hydraulic residence time throughout the Delta. Turbidity levels, which positively affect both
- 13 risk of predation and foraging efficiency of delta smelt, would likely be highest under Option 4.
- The quantity, quality, and accessibility of probable spawning habitat would be the greatest
- under Option 4 by allowing the greatest area of the Delta to be available for restoration.
- under Option 4 by anowing the greatest area of the Delta to be available for restoration.
- 16 CVP/SWP entrainment of delta smelt would be virtually eliminated under Option 4 because
- there would be no south Delta diversions and the Hood diversion is located upstream of the
- main distribution of the delta smelt population. One major stressor to delta smelt that Option 4
- 19 could increase is exposure to toxics as a result of reduced Sacramento River dilution flows and
- 20 increased relative contribution of lower quality San Joaquin River water. Opportunities for
- 21 pollutant source control to reduce the potential risk of toxicity effects would be equally
- 22 applicable across all Options.

7.1.2 Longfin Smelt

- Option 4 would allow the greatest benefit to longfin smelt because it performs best in relieving
- 25 highly important and moderately important stressors (see Table 7-5). Option 3 would provide
- 26 the second greatest benefit to longfin smelt, Option 2 would rank third, and Option 1 would
- 27 provide the lowest benefit to longfin smelt because it relieved stressors the least amount. All
- Options, however, provide benefits for delta smelt relative to base conditions.
- 29 Option 1 would provide the lowest benefit to longfin smelt. Although Option 1 would relieve
- 30 multiple stressors, it consistently ranks lowest in performance among the Options. Option 1
- 31 would rank lowest in potential benefits to longfin smelt in terms of quantity and quality of food,
- 32 rearing and spawning habitat, turbidity, predation, and CVP/SWP entrainment. Option 1
- 33 performs best among the Options in reducing exposure of longfin smelt to toxics, though this
- 34 effect is identical to base conditions.

Table 7-5. Summary of Option Effects on Important Longfin Smelt Stressors

C1	Option Eff	ects Relative to I	mportant Specie	s Stressors
Stressors ¹	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important Stressors				
Reduced access to spawning habitat	8	8	0	8
Treateed decess to sparring habitat	2	2	2	2
Poduced access rearing habitat	\otimes	⊗	••	•
Reduced access rearing habitat	3	3	3	3
Reduced food	•	••	•••	••••
	3	3	3	3
Predation	••	•••	•••	••••
	1	1	1	1
Reduced turbidity	•	••	•••	•••
	3	3	3	3
Reduced energying hebitat	•	••	••	••••
Reduced spawning habitat	2	2	2	2
Doduced food quality	•	•••	•••	••••
Reduced food quality	1	1	1	1
Moderately Important Stressors				
CVD/CVAD and an immedia	8	••	••••	••••
CVP/SWP entrainment	4	2	3	4
D 1 1 1 1111	8	8	••	••
Reduced rearing habitat	3	3	3	3
Turan ta tanàn	8	00	000	000
Exposure to toxics	4	1	1	1

Notes:

1

- . See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- 2. Effects (relative to base conditions):
 - = very low benefit,
 - •• = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - = very low adverse effect,
 - oo = low adverse effect,
 - ooo = moderate adverse effect,
 - 0000 = high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

- Option 2 would provide the third highest benefit to longfin smelt. Like Option 3, Option 2
- 3 would need to rely on the use of the Middle River channel for water conveyance to the export
- 4 facilities and maintain export water quality standards in the south Delta, but, unlike Option 3,
- 5 this need would extend to all flow conditions in all water year types under Option 2. Therefore,
- 6 the ability to increase food quantity and accessibility and increase turbidity would be reduced
- 7 under Option 2. Entrainment at CVP/SWP pumps would increase under Option 2 when
- 8 compared with operations under either Options 3 or 4.

Option 3 would provide the second highest benefit to longfin smelt. A primary difference 1 2 between Option 3 and Option 4 is the requirement under Option 3 to meet export water quality standards in the south Delta when south Delta pump facilities are operating, resulting in a 3 4 reduced area available for potential habitat restoration. In addition, operation under Option 3 would continue to use Middle River as the primary pathway for water conveyance from the 5 Sacramento River to the south Delta export facilities and therefore would degrade opportunities 6 for habitat enhancement in the Middle River area and east side tributaries. Along with Option 7 4, Option 3 provides the best opportunity to increase turbidity and reduce CVP/SWP 8 9 entrainment. Option 3 provides the second highest opportunity (after Option 4) to increase longfin smelt rearing and spawning habitat, increase food quantity, quality, and accessibility, 10 and reduce predation by non-natives. 11

Option 4 would provide the greatest benefit to longfin smelt among the Options because it would provide the best opportunity to relieve multiple highly important stressors. Option 4 provides the greatest increase in food quantity and quality by providing the largest area, with the greatest geographic distribution, in which to restore habitat that, if appropriately designed, would promote abundances native prey species and reduce abundances of non-native competitors. Option 4 also provide hydrodynamic conditions, including reduced channel velocities and increased residence times, that would be expected to result in greater phytoplankton and zooplankton production within the Delta. Food quantity would also likely increase under Option 4 by reducing exports of nutrients and organic carbon by CVP/SWP pumps and increasing hydraulic residence time throughout the Delta. Turbidity levels would likely be greatest under Option 4. The quantity, quality, and accessibility of probable spawning habitat would be the greatest under Option 4 by allowing the largest area of the Delta to be available for restoration. Option 4 would also rank highest in reducing the risk of predation by non-native species by providing the greatest area of the Delta to be available for restoration, which, if appropriately designed, would reduce conditions for non-native predators. CVP/SWP entrainment of longfin smelt would decrease under Option 4 because there would be no south Delta diversions and the Hood diversion is upstream of the main distribution of the longfin smelt population. In addition, the diversion at Hood would be equipped with a stateof-the-art positive barrier fish screen that would be expected to effectively exclude juvenile and adult longfin smelt, and other fish species, from being entrained as a result of diversion operations. One major stressor to longfin smelt that Option 4 could increase is exposure to toxics due to reduced Sacramento River dilution flows and increased relative contribution of lower quality San Joaquin River water.

7.1.3 Sacramento River Salmonids

12

13

14

1516

17

18

19

2021

2223

24

25

2627

28

29 30

31

32

33

34

- 36 Option 4 is expected to provide the highest level of benefit for Sacramento River salmonids
- 37 relative to base conditions and the other Options. Options 1, 2, and 3 would all be expected to
- 38 provide similar benefits (Tables 7-6 and 7-7).
- 39 The evaluation only addressed flow conditions that would facilitate access of salmonids to
- 40 staging and spawning habitats because those habitats are located upstream of the planning
- area. Both Chinook salmon (fall-/late fall-run, spring-run, and winter-run) and Central Valley
- 42 steelhead located in the Sacramento River were combined in this summary because results of
- 43 the evaluation of each Options were the same among the runs and species.

- 1 The overall performances of Options 1, 2, and 3 for Sacramento River salmonids are largely
- 2 indistinguishable. Each Option scores highly with respect to relieving some stressors and
- 3 poorly with respect to relieving others. For example, Option 3 performs well with respect to
- 4 CVP/SWP entrainment, but scores poorly with respect to exposure to toxics. Options 1 and 2
- 5 perform well in reducing rearing and spawning habitat, but have no other benefits to
- 6 Sacramento River salmonids. Because of the high natural variability and resulting level of
- 7 uncertainty associated with the Delta ecosystem, it is not possible to distinguish among these
- 8 Options with reasonable confidence.
- 9 Option 4 would perform best among the Options for Sacramento River salmonids because it
- would relieve, to the greatest degree, all of the stressors identified as highly important
- including non-native predation, rearing and outmigration habitat, staging and spawning
- 12 habitat, and CVP/SWP entrainment.

Table 7-6. Summary of Option Effects on Important Sacramento River Chinook Salmon Stressors

Stressors ¹	Option Effect	ts Relative to In	nportant Speci	es Stressors
	Option 12,3	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important Stressors				
Dodres data sing and an assuring helitat	8	8	0	•
Reduced staging and spawning habitat	2	2	2	2
Reduced rearing and outmigration habitat	••	••	•	•••
Reduced rearing and outningration habitat	3	3	3	3
Predation by non-native species	••	••	••	••••
1 redation by non-native species	1	1	1	1
Moderately Important Stressors				
Harvest	8	8	8	8
Tarvest	4	4	4	4
Reduced genetic diversity/ integrity	8	8	8	8
Reduced genetic diversity/ integrity	4	4	4	4
CVP/SWP entrainment	⊗	⊗	•••	••••
CVI/3VVI entraniment	4	3	3	3
Truncaruma to torrino	8	8	000	000
Exposure to toxics	4	1	1	1
In annual of street on towns on a true	8	8	8	8
Increased water temperature	4	4	4	4

Notes:

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
 - . Effects (relative to base conditions):
 - = very low benefit,
 - $\bullet \bullet$ = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - \circ = very low adverse effect,
 - $\circ \circ$ = low adverse effect,
 - $\circ \circ \circ =$ moderate adverse effect,
 - $\circ \circ \circ \circ =$ high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

Relative degree of certainty assigned here is based on a qualitative combination of the certainty levels assigned to impact mechanisms relative to stressors (Appendix C) and the certainty level assigned to tools relative to metrics (Section 2).

13

Table 7-7. Summary of Option Effects on Important Sacramento River Steelhead Stressors

Stressors ¹	Option Effe	cts Relative to In	portant Species	s Stressors
	Option 12,3	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important Stressors				
Reduced staging and spawning habitat	8	8	0	•
	2	2	2	2
CVD (CVAID and an in many)	8	8	•••	••••
CVP/SWP entrainment	4	3	3	3
Reduced rearing and outmigration	••	••	•	•••
habitat	3	3	3	3
Due dation because native energies	••	••	••	••••
Predation by non-native species	1	1	1	1
Moderately Important Stressors	•			
F	8	8	000	000
Exposure to toxics	4	1	1	1
De least a matter than matter / test a matter	8	8	8	8
Reduced genetic diversity/ integrity	4	4	4	4
Harvest	8	8	8	8
Tiaivest	4	4	4	4
Increased water temperature	8	8	8	8
nicreased water temperature	4	4	4	4

Notes:

1

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- 2. Effects (relative to base conditions):
 - = very low benefit,
 - $\bullet \bullet$ = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - \circ = very low adverse effect,
 - $\circ \circ = low adverse effect,$
 - ooo = moderate adverse effect,
 - 0000 = high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

Relative degree of certainty assigned here is based on a qualitative combination of the certainty levels assigned to impact mechanisms relative to stressors (Appendix C) and the certainty level assigned to tools relative to metrics (Section 2).

2 7.1.4 San Joaquin River Salmonids

- 3 Option 4 would provide the greatest benefit to San Joaquin River salmonids because it ranks
- 4 consistently best in relieving highly important and moderately important stressors (see Tables
- 5 7-8 and 7-9). Option 3 would provide the second greatest benefit to San Joaquin River
- 6 salmonids, followed by Option 2. Option 1 would provide the lowest benefit to San Joaquin
- 7 River salmonids because it consistently ranked lowest in relieving important stressors to San
- 8 Joaquin River salmonids.
- 9 Based on the evaluation of the potential effects of the Options on important San Joaquin River
- salmonid stressors (Tables 7-8 and 7-9), Option 1 is expected to provide the lowest level of

Table 7-8. Summary of Option Effects on Important San Joaquin River **Chinook Salmon Stressors**

C1	Option Effects Relative to Important Species Stressors					
Stressors ¹	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}		
Highly Important Stressors	5	<u> </u>				
Reduced staging and	8	8	•	••		
spawning habitat	3	2	2	2		
Reduced rearing and	••	••	••	•••		
outmigration habitat	3	2	2	3		
Europeumo to touigo	8	00	000	000		
Exposure to toxics	4	1	1	1		
Predation by non-native	•	••	••	••••		
species	1	1	1	1		
Moderately Important Stre	ssors					
Reduced genetic	8	8	8	8		
diversity/ integrity	4	4	4	4		
Harvest	8	8	8	8		
Harvest	4	4	4	4		
CVP/SWP entrainment	\otimes	•	•••	••••		
CV1/3W1 entraniment	4	3	3	3		
Increased water	\otimes	8	8	8		
temperature	4	4	4	4		

Notes:

- See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- Effects (relative to base conditions):
 - = very low benefit,
 - $\bullet \bullet$ = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - o = very low adverse effect,
 - oo = low adverse effect,
 - $\circ \circ \circ =$ moderate adverse effect,
 - 0000 = high adverse effect.
- Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:

 - 4 = High 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

Relative degree of certainty assigned here is based on a qualitative combination of the certainty levels assigned to impact mechanisms relative to stressors (Appendix C) and the certainty level assigned to tools relative to metrics (Section 2).

1 Table 7-9. Summary of Option Effects on Important San Joaquin River Steelhead Stressors

C1	Option	Effects Relative to	Important Species S	tressors
Stressors ¹	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important	Stressors			
Reduced staging and spawning habitat	⊗ 3	⊗ 2	• 2	2
Reduced rearing and outmigration habitat	• 3	2	2	3
Exposure to toxics	⊗ 4	00 1	000 1	000 1
Reduced genetic diversity/ integrity	⊗ 4	⊗ 4	⊗ 4	⊗ 4
Predation by non-native species	• 1	1	1	1
Moderately Impor	tant Stressors			
CVP/SWP entrainment	• 4	• 3	3	3
Harvest	⊗ 4	⊗ 4	⊗ 4	⊗ 4
Increased water temperature	⊗ 4	⊗ 4	⊗ 4	⊗ 4

Notes:

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- 2. Effects (relative to base conditions):
 - = very low benefit,
 - •• = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - o = very low adverse effect,
 - oo = low adverse effect,
 - $\circ \circ \circ =$ moderate adverse effect,
 - $\circ\circ\circ\circ$ = high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

- 2 benefits relative to base conditions and the other Options because it consistently provides the
- 3 lowest benefit to reducing the effects of both very high and moderately high stressors. The only
- 4 stressor for which Option 1 would provide the greatest benefit is the exposure of San Joaquin
- 5 River salmonids to toxics, but this effect would be no greater than base conditions. Option 2 is
- 6 expected to provide the third highest benefit to San Joaquin River salmonids. Option 2 is
- 7 expected to perform marginally better than Option 1 by providing increased rearing and
- 8 outmigration habitat and reducing the risk to predation by non-native species. Option 2 would

7.0 Comparison of the Options Relative to Biological Criteria September 17, 2007

- 1 perform lower than Option 1 with respect to exposure to toxics. It is expected that the effects of
- 2 Option 2 on all other stressors will be similar to Option 1.
- 3 Option 3 is expected to provide the second highest benefit to San Joaquin River salmonids.
- 4 Option 3 is expected to perform marginally better than Option 2 by providing increased staging
- 5 and spawning habitat and reducing entrainment risk. Option 3 would perform lower than
- 6 Option 2 with respect to exposure to toxics. It is expected that the effects of Option 3 on all
- 7 other stressors will be similar to Option 2.
- 8 Option 4 is expected provide the highest level of benefit relative to base conditions and the
- 9 other Options because it is likely to be more effective than the other Options in:
- improving access to staging and spawning habitat,
- improving rearing and outmigration habitat conditions,
- reducing predation risk, and
- reducing SWP/CVP entrainment risk.

14 7.1.5 Green and White Sturgeon

- 15 The important stressors for green and white sturgeon that are addressed by each of the Options
- 16 include exposure to toxics and reduced rearing habitat. The remaining important stressors for
- 17 this species can only be addressed outside of the planning area (see Appendix C). Option 4
- 18 would be expected to have a moderate beneficial effect relative to base conditions and would be
- 19 expected to provide the greatest benefit among the Options for green and white sturgeon
- 20 (Tables 7-10 and 7-11). Options 2 and 3 would have a low beneficial effect relative to base
- 21 conditions for both sturgeon species. Option 1 is expected to provide a low benefit for green
- sturgeon and a very low benefit for white sturgeon relative to base conditions (Tables 7-10 and
- 23 7-11).
- 24 Based on the evaluation of the potential effects of the Options on sturgeon stressors (Tables 7-10
- and 7-11), Options 1, 2, and 3 are expected to provide a low level of benefit for green sturgeon
- 26 relative to base conditions. These Options provide a lower level of benefit than under Option 4
- 27 because they provide fewer geographic opportunities for restoring habitat in the range of the
- 28 green sturgeon within the planning. Option 1 is expected to provide a very low level of benefit
- 29 for white sturgeon relative to base conditions and the other Options because it provides the
- 30 fewest opportunities for restoring habitat in the range of the white sturgeon within the planning
- 31 area.
- 32 Options 2 and 3 are expected to provide a low level of benefit to white sturgeon relative to base
- conditions, a higher benefit relative to Option 1, and a lower level of benefit relative to Option 4
- 34 because these Options provide greater geographic opportunities for restoring habitats in the
- 35 Delta relative to Option 1, but fewer opportunities relative to Option 4.

1 Table 7-10. Summary of Option Effects on Important Green Sturgeon Stressors

Stressors ¹	Option Eff	ects Relative to I	nportant Sp	ecies Stressors
Stressors	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 32,3	Option 4 ^{2,3}
Highly Important Stressors				
Reduced spawning habitat	⊗	8	8	8
Reduced spawning nabitat	3	3	3	3
Exposure to toxics	8	8	000	000
	4	1	1	1
Harvest	8	8	8	8
	4	4	4	4
Moderately Important Stressors				·
D. J. and marking helding	••	••	••	•••
Reduced rearing habitat	3	3	3	3
Increased water temperature	8	8	8	8
(upstream)	3	3	3	3
Duodation	8	8	8	8
Predation	4	4	4	4
Doduced trubidity	8	8	8	8
Reduced turbidity	4	4	4	4

Notes:

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- 2. Effects (relative to base conditions):
 - = very low benefit,
 - •• = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - \circ = very low adverse effect,
 - oo = low adverse effect,
 - ooo = moderate adverse effect,
 - $\circ \circ \circ \circ =$ high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

Table 7-11. Summary of Option Effects on Important White Sturgeon Stressors

C11	Option Effec	cts Relative to l	Important Spec	cies Stressors
Stressors ¹	Option 12,3	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important Stressors				
Harvest	8	8	8	8
	4	4	4	4
Reduced spawning habitat	8	8	8	8
	3	3	3	3
Exposure to toxics	8	0	000	000
	4	1	1	1
Moderately Important Stressors	•			
Doduced accesses helitat	•	••	••	•••
Reduced rearing habitat	3	3	3	3
I a series de la companya (constante)	8	8	8	8
Increased water temperature (upstream)	3	3	3	3
Don follow	8	8	8	8
Predation	4	4	4	4
Dodgood tookidite	8	8	8	8
Reduced turbidity	4	4	4	4

Notes:

1

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- . Effects (relative to base conditions):
 - = very low benefit,
 - •• = low benefit,
 - ••• = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - \circ = very low adverse effect,
 - oo = low adverse effect,
 - $\circ \circ \circ =$ moderate adverse effect,
 - 0000 = high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

- 2 Option 4 is expected to provide a moderate benefit for green and white sturgeon relative to base
- 3 conditions and the greatest benefit among the Options because it provides greater geographic
- 4 opportunities for restoring aquatic shallow water subtidal and intertidal habitats. Unlike
- 5 Options 1 and 2, there would be a reduction in Delta inflows under Options 3 and 4 that could
- 6 have a low adverse effect on exposure of sturgeon to toxics because the ability of inflows to
- 7 dilute toxic concentrations would be reduced.
- 8 Options 3 and 4 perform lower than Options 1 and 2 with regard to exposure of green sturgeon
- 9 and white sturgeon to toxics because Sacramento River inflows to the Delta, which are assumed
- to dilute concentrations of toxics, are lower relative to base conditions and Options 1 and 2.
- 11 However, the effects of reductions in Sacramento River inflows under Options 3 and 4 on
- increasing the exposure of sturgeon to toxics are highly uncertain. Allowing San Joaquin River
- water, which has a high selenium load, to discharge into the Delta with reduced dilution from
- the Sacramento River under Options 2, 3, and 4 could increase the bioaccumulation of selenium

- 1 in sturgeon. This evaluation assumes that, because source control reductions in San Joaquin
- 2 River selenium loads have been mandated by the Regional Water Quality Board to be in place
- 3 by 2012, selenium concentrations would not become elevated from base conditions under
- 4 Options 2, 3, and 4. If source controls are unsuccessful and selenium concentrations were to
- 5 increase in the Delta, Options 2, 3, and 4 would be expected to have an overall adverse effect on
- 6 sturgeon.

14

7.1.6 Sacramento Splittail

- 8 The important stressors on Sacramento splittail that are addressed by each of the Options
- 9 include reduced juvenile rearing/adult habitat; reduced food availability; reduced
- spawning/larval rearing habitat; exposure to toxics; predation; and SWP/CVP entrainment
- 11 (Appendix C). Based on the evaluation of the potential effects of the Options on important
- splittail stressors (see Table 7-12), Option 4 is expected provide the highest level of benefit
- relative to base conditions. Option 3 is expected to perform better than Options 1 and 2.

Table 7-12. Summary of Option Effects on Important Sacramento Splittail Stressors

Ctuacacus1	Option Effe	ects Relative to	Important Speci	es Stressors
Stressors ¹	Option 1 ^{2,3}	Option 2 ^{2,3}	Option 3 ^{2,3}	Option 4 ^{2,3}
Highly Important Stressors				
Reduced juvenile rearing/adult habitat	3	•• 3	3	3
Reduced spawning/larval rearing habitat	3	3	3	3
Reduced food	• 3	3	3	3
Exposure to toxics	⊗ 3	°° 3	000 3	3
Moderately Important Stressors				
Predation	3	3	3	3
SWP/CVP entrainment	• 3	3	3	3
Harvest	⊗ 4	⊗ 4	⊗ 4	⊗ 4

Notes:

- 1. See Appendix C for descriptions of stressors, stressor impact mechanisms, and stressor effects.
- 2. Effects (relative to base conditions):
 - \bullet = very low benefit,
 - •• = low benefit,
 - $\bullet \bullet \bullet$ = moderate benefit,
 - •••• =high,
 - ⊗ = no change,
 - \circ = very low adverse effect,
 - $\circ \circ = low adverse effect,$
 - ooo = moderate adverse effect,
 - 0000 = high adverse effect.
- 3. Relative degree of certainty (indicated below the effects symbols) of the magnitude of Option effect on the stressor:
 - 4 = High
 - 3 = Moderate
 - 2 = Low
 - 1 = little or no certainty.

- Options 1 and 2 would be expected to provide a low level of benefit relative to base conditions
- 2 and lower levels of benefit compared to Options 3 and 4 primarily because they are not
- 3 expected to improve food availability or address entrainment as effectively as those Options.
- 4 Option 3 is expected to perform better than Options 1 and 2, because it is more likely to
- 5 improve habitat conditions and food availability and reduce the effects of entrainment losses to
- 6 a greater extent than those Options.

11

17

18

- 7 Option 4 is expected to provide a greater level of benefit than the other Options because it is
- 8 more likely to improve habitat conditions and food availability and reduce effects of predation
- 9 and entrainment losses to a similar or greater degree than the other Options.

7.2 COMPARISON OF THE OPTIONS RELATIVE TO THE PLANNING CRITERIA

- 12 This section provides a comparison of the performance of each Option relative to each of the
- planning criteria based on the planning criteria evaluations presented in Sections 3.2, 4.2, 5.2,
- and 6.2. Table 7-13 presents a summary description of the performance of each Option relative
- to the planning criteria evaluation metrics. Table 7-2 presents a comparison of the performance
- of each Option relative to each of the planning criteria.

Table 7-13. Comparison of the Performance of the Options Relative to the Planning Criteria Metrics¹

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4
		ne Option allows cover orposes of those activit		lemented in a way
P1. Water supply reliability	Low - continued regulatory restrictions would reduce reliability	Moderate – engineered solution to limiting gravity siphon would increase export capability	High – dual system provides greatest reliability of export operations	Moderate – isolated conveyance reduces regulatory constraints; limits due to loss of San Joaquin and east side supplies
P2. Operational flexibility	Very Low – single source in south Delta with regulatory constraints	Very Low – single source in south Delta with regulatory constraints	High – dual system provides greatest flexibility of export operations	Moderate – regulatory constraints mostly avoided but single source from Sacramento R. is limiting
P3. Quality of water exported from the SWP/CVP facilities	Very Low – continued issues with salts and organics	Low -improvement in water quality over Option 1 with separation from San Joaquin R.	Moderate – dominated by high quality Sacramento R. water	High – all high quality Sacramento R. water

Table 7-13. Comparison of the Performance of the Options Relative to the Planning Criteria Metrics¹ (continued)

Metric	Option 1	Option 2	Option 3	Option 4
C 14 1 #0 FF1	_	(with pump)		_
	relative feasibility and neer, and implement	practicability of the C	Option, including the a	bility to fund,
P4. Relative	Moderate – ,	Moderate –	Moderate – some	Moderate – some
feasibility and	constraints to	technological	technological	technological
practicability to	achieving	challenges and	challenges,	challenges,
address habitat	conservation and	constraints to	flexibility to achieve	flexibility to achieve
conservation and	supply goals;	achieving dual	dual goals, many	dual goals, many
water supply goals	regulatory	goals	regulatory	regulatory
water suppry gours	constraints	Some	approvals	approvals
Criterion #10. Relat	tive costs (including in	frastructure, operation		1 1 1 1 1 1
	ciated with implement		is, una management,	
P5. Ability to	High - no new	Moderate -	Very Low - likely	Low - likely to have
control construction	facility construction	substantially	to have greater	lower construction
costs for	costs	smaller	construction costs	costs (\$3.6-5.0B)
implementing the		construction cost	(\$3.5-8.8B) than	than Option 3, but
Option		(\$0.5-2.8B) relative	Option 4, but	substantially higher
		to Options 3 and 4	substantially higher	costs than Option 2
			costs than Option 2	
		frastructure, operation	ns, and management)	associated with
_	ementing the Option.	1	1	
P5. Ability to	High - no new	Moderate -	Very Low – likely	Low - likely to have
control construction	facility construction	substantially	to have greater	lower construction
costs for	costs	smaller	construction costs	costs (\$3.6-5.0B)
implementing the		construction cost	(\$3.5-8.8B) than	than Option 3, but
Option		(\$0.5-2.8B) relative	Option 4, but	substantially higher
		to Options 3 and 4	substantially higher	costs than Option 2
			costs than Option 2	
P6. Ability to avoid	Very Low - No	Moderate -	High- Potential	High- Potential
redirected costs to	export water	Potential savings in	savings in water	savings in water
service areas from	quality	water treatment	treatment costs of	treatment costs of
adverse effects of	improvement	costs of \$1.0-\$1.5	\$1.5-\$2.0 billion	\$2.0-\$2.5 billion
low water quality	relative to current	billion over the next	over the next 25	over the next 25
on municipal	condition. No	25 years.	years; reduced salt	years; reduced salt
treatment,	savings in water		build-up rate on	build-up rate on
agricultural	treatment costs;		farmland; reduced	farmland; reduced
production, and human health	continued salt		human health	human health
numan neaitn	build-up on		issues/costs	issues/costs
	farmland; long-term			
	human health issues/costs			
	issues/ costs			

2

Table 7-13. Comparison of the Performance of the Options Relative to the Planning Criteria Metrics¹ (continued)

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4		
	Criterion #10. Relative costs (including infrastructure, operations, and management) associated with implementing the Option.					
P7. Ability to avoid costs for extensive and frequent recovery and repair following catastrophic events Noderate - Reinforced levees and export disruption costs; 50% chance over next 25 years of major disruption in Delta exports resulting in tens of billions of dollars in economic damages 1, but still sizable risk from levee failures resulting in water supply disruption. 1, but still sizable risk from levee failures requent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost with less extensive and less frequent losses from seismic or 1, but still one cost water supply reduces risks to water supply from levee failures. Potential savings of \$10's billions over long term. Dual system provides most flexibility to reduces risks to water supply reduces risks to water supply from levee failures. Potential savings of \$10's billions over long term. Dual system provides water supply reduces risks to water supply reduces risks						

7.21.1 Criterion #8. Relative degree to which the Option allows covered activities to be implemented in a way that meets the goals and purposes of those activities.

- 4 Criterion #8 addresses the ability of the Options to achieve the water supply goals of the CVP
- 5 and SWP. For the purposes of this evaluation, CVP/SWP export water reliability, project
- 6 operational flexibility, and export water quality were used for describing the relative capability
- of each Option to meet this criterion. Option 3 is expected to perform the best with regard to
- 8 meeting the goals and purposes of the covered activities, with Option 4 second (Table 7-13).
- 9 Option 2 is ranked third and Option 1 fourth.
- 10 Option 1 has the lowest export water quality with highest salinity and organics. Although the
- existing engineered system of Option 1 allows for high export reliability, regulatory restrictions
- 12 significantly reduce reliability with the Option 1 structural configuration of through-Delta
- 13 conveyance and limited protection of fish from pump facilities.
- Option 2 provides higher quality water than Option 1, but the gravity-fed siphon appears to be
- a design flaw that would need to be solved for Option 2 to provide reliable water supply.
- Assuming an engineered solution with a low-head pump facility at the siphon under Option 2,
- anticipated water supply reliability is expected to be equal to or higher than Option 1 and base
- 18 conditions. Physical constraints to operations (i.e., channel capacity of Victoria Canal) would
- 19 need to be addressed for Option 2 to function in meeting supply reliability goals.

- 1 Hydrodynamic modeling results suggest that Option 3 provides the greatest combination of
- 2 water supply reliability, flexibility of operations, and water quality. The dual facility operation
- 3 allows opportunistic use of the most effective and efficient facility when hydrologic,
- 4 hydrodynamic, and regulatory conditions limit the use of the other facility.
- 5 Option 4 performs well in meeting the goals of the covered activities, but its water reliability is
- 6 constrained by the reliance on Sacramento River water only with the intake isolated from using
- 7 east side tributary and San Joaquin River waters. Export water quality under Option 4 is
- 8 consistently the highest of all Options.

9 7.2.1.2 Criterion #9. The relative feasibility and practicability of the Option, including the ability to fund, engineer, and implement.

- 11 Criterion #9 addresses the feasibility and practicability of implementing each of the Options.
- 12 The evaluation of this criterion was based on a qualitative assessment of the certainty of
- technologies for successfully engineering new facilities, likely level of regulatory uncertainties,
- implementation cost, and practicability of the Option to meet both planning and conservation
- goals. All Options were determined to be of equivalent feasibility and practicability with each
- Option having different strengths and constraints contributing to this conclusion (Table 7-13).
- 17 While Option 1 could be considered the most feasible Option because it would be of lowest
- 18 initial cost, would not test any new technologies, and would avoid the new regulatory
- 19 compliance, this Option does not offer a strong solution to meeting the key goals of species
- 20 conservation and water supply reliability and would continue to face regulatory uncertainty for
- 21 Delta operations. Option 1 is considered of moderate feasibility.
- 22 Option 2 would require some technological challenges in developing a siphon and pump
- 23 system, modifying channels to support high flows, and operating the barriers to maximize
- 24 opportunities for both conservation and water supply conveyance. Option 2 is considered of
- 25 moderate feasibility.
- 26 Option 3 provides a flexible approach to addressing the combined goals of species conservation
- 27 and habitat restoration using practicable technologies. This Option has the highest initial
- 28 construction costs and construction of the both peripheral aqueduct and in-Delta facilities
- 29 would require challenging regulatory compliance. Option 3 is considered of moderate
- 30 feasibility.
- 31 Option 4 provides a highly flexible approach to addressing the combined goals of species
- 32 conservation and habitat restoration using practicable technologies. Construction of the
- 33 peripheral aqueduct would require challenging regulatory compliance and substantial cost.
- 34 Option 4 is considered of moderate feasibility.

7.2.1.3 Criterion #10. Relative costs (including infrastructure, operations, and management) associated with implementing the Option.

- 37 The Options were evaluated in terms of expected construction costs, Delta conveyance
- disruption costs, and redirected water quality costs. Because this evaluation assumes that the
- overall amount of habitat restoration would be roughly the same for each Option, costs for

habitat restoration were not used to differentiate the four Options and therefore were not calculated. It is important to emphasize that much of the data and information relied on for the cost evaluation was cursory in nature. In all cases professional judgment was used to assess order-of-magnitude and relative costs. Key parts of the evaluation relied on information developed for the Delta Risk Management Strategy (Draft Phase I and Draft Phase II Reports 2007), some of which may be revised or updated as work products from that effort are refined and finalized. As new information comes to light the ordering of relative costs presented here could be affected. Therefore findings regarding the relative costs of the four Options should be viewed as preliminary rather than definitive. For example, the cost analysis does not include an assumption that levee improvements might be conducted by other programs for other reasons with associated direct cost savings and economic benefits to in-Delta uses such as species conservation.

The evaluation concluded that Option 4 would have the lowest long-term costs with Option 3 slightly higher or equivalent to Option 4. Option 2 ranked third because the long-term cost savings were estimated to be less than Options 3 and 4. The cost of Option 1 was estimated to

be the highest as a result of on-going costs over the long-term.

Option 1 is anticipated to have the highest overall cost of all Options over the long term. While the cost of construction is anticipated to be much lower¹ than the other Options, the periodic cost of recovery from seismic and flood events and the on-going cost of municipal water treatment are expected to overcome the construction cost savings over time. Anticipated risk and cost of catastrophic loss under Option 1 is much higher than other Options, possibly as much as \$10-50 Billion in costs at a 50% chance of occurrence in the next 25 years. Option 1 is not expected to significantly improve water quality over existing conditions and therefore would not accrue the substantial water treatment cost savings as other Options – ranging from \$1.0-2.5 Billion over the next 25 years.

Options 2 would have a higher overall cost than Options 3 and 4 and a lower overall cost than Option 1. While construction costs for Option 2 are \$3 to \$5 billion less than Option 3 and \$3 to \$4.5 billion less than Option 4, the risk of catastrophic loss of conveyance and the cost for recovery from such events under Option 2 is much higher than under Options 3 and 4 and the cost savings to water treatment in service areas is less under Option 2 than under Options 3 and 4. For these reasons, Option 2 is anticipated to result in higher overall costs over the long term than Options 3 and 4. Option 2 would have lower overall cost than Option 1 because the savings over time in recovery costs from seismic or flood events and in water treatment costs under Options 2 is anticipated to overcome the initial \$0.5-2.8 billion higher construction costs.

Option 3 would be expected to have the second lowest overall cost over the long term. This low cost is the result of savings from lower frequency of catastrophic events shutting down the water supply system and lower per-event costs for recovery from catastrophic events, and from substantial on-going savings resulting from reduced costs for water treatment in service areas. These savings are expected to recover over time the construction cost differences between Option 3 and Options 1 and 2. Option 3, as configured, is considered more expensive than

¹ Note, however, that additional construction cost under Option 1 to improve CVP and SWP screening and salvage facilities could be on the order of \$1.3 billion and were not included in the cost comparison here.

- 1 Option 4 because the initial construction costs would be higher, on-going operational costs
- 2 would be higher (operating and maintaining 2 facilities rather than 1), and savings on water
- 3 treatment costs would be less. The on-going cost of Option 3, however, could be reduced by the
- 4 value of increased water delivery capability from the operational flexibility provided by
- 5 multiple intakes. Option 3 may have a lower risk of supply cutoff from seismic or flood events
- 6 and, therefore, a lower long-term cost for recovery following catastrophic events than Option 4,
- 7 but it cannot be concluded whether this difference is substantial enough to offset other costs
- 8 over time.

16

21

22

- 9 Option 4 would be expected to have the lowest overall cost over the long term (Table 7-13). This
- 10 low cost is the result of savings from lower frequency of catastrophic events shutting down the
- 11 water supply system and lower per-event costs for recovery from catastrophic events, and from
- substantial on-going savings resulting from reduced costs for water treatment in service areas.
- 13 These savings are expected to recover over time the construction cost differences between
- 14 Option 4 and Options 1 and 2.

7.3 COMPARISON OF THE OPTIONS RELATIVE TO FLEXIBILITY/ DURABILITY/ SUSTAINABILITY CRITERIA

- 17 This section provides a comparison of the performance of each Option relative to each of the
- criteria based on the evaluations presented in Sections 3.3, 4.3, 5.3, and 6.3. Table 7-14 presents a
- 19 summary description of the performance of each Option relative to the evaluation metrics and
- 20 Table 7-2 compares the performance of each Option relative to each of the criteria.

Table 7-14. Comparison of the Performance of the Options Relative to Flexibility/Durability/Sustainability Criteria Metric¹

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4
Criterion #11. Relat	ive degree to which th	e Option will be able	to withstand the effect	ts of climate change
(e.g.,	sea level rise, changes	in runoff), variable hy	drology, seismic even	ts, subsidence of
Delta	islands, and other lar	ge-scale changes to the	e Delta.	
F1. Ability of	Very Low – no	Low – new levees	High – peripheral	High – peripheral
infrastructure	protective upgrades	provide some	aqueduct is more	aqueduct is more
supporting	to conveyance	protection to	durable to seismic	durable to seismic
conveyance to	facilities	conveyance	and flood events	and flood events
avoid disruption in		facilities in south	than through-Delta	than through -Delta
water supply		Delta but not in	conveyance and	conveyance
resulting from		north Delta	redundancy of dual	
effects of seismic			system provides	
and flood events			extra protection	
and sea level rise			-	
F2. Ability of the	Low – least	Moderate - more	Moderate - more	High – large area
Option to avoid loss	flexibility for	area than Option 1	area than Option 1	for locating
of restored habitat	locating restoration	but less than Option	but less than Option	restoration provides
from future seismic	to adapt to sea level	4 for locating	4 for locating	more opportunity
and flood events	rise and avoid	restoration to avoid	restoration to avoid	for locating sites to
and sea level rise	catastrophic loss	large losses	large losses	address sea level
	_			rise and avoid
				catastrophic loss

Table 7-14. Comparison of the Performance of the Options Relative to Flexibility/Durability/Sustainability Criteria Metric¹ (continued)

<u> </u>	Flexibility/Durability/Sustainability Criteria Metric1 (continued)					
Metric	Option 1	Option 2 (with pump)	Option 3	Option 4		
	long term needs of each of the covered species and their habitats with minimal future input					
	sources.		T	ı		
F3. Ability of the	Low – ongoing	Low - ongoing	Moderate – dual	High – greatest		
Option to support	costs associated	costs associated	conveyance feature	opportunities to		
species	with mitigating	with mitigating	provides	adaptively		
conservation	entrainment losses	entrainment losses	opportunities to	managing habitat		
without continual	(likely more than	(likely less than	reduce entrainment	restoration and		
input of large	Option 2) and very	Option 1) and	mitigation costs and	Delta flow patterns		
amounts of	limited flexibility	limited flexibility	some flexibility for	to benefit fish		
resources to	for adaptively	for adaptively	adaptively	species; minimal		
maintain	managing Delta	managing Delta	managing Delta	ongoing		
conservation	flow patterns	flow patterns	flow patterns	entrainment		
benefits		•	1	mitigation costs		
Criterion #13. Relat	tive degree to which th	e Option can be adapt	ed to address needs of	covered fish species		
over	_			•		
F4. Flexibility to	Low – existing	Low – operable	Moderate – dual	High – greatest		
experiment with	conveyance	barriers provide	conveyance feature	opportunities for		
and adjust water	configuration	limited flexibility	provides more	adaptively		
management to	presents few	for adaptively	flexibility to	managing Delta		
address current and	opportunities for	managing Delta	adaptively	flow patterns across		
future ecological	managing Delta	flow patterns	managing Delta	large area to benefit		
uncertainties to	flow patterns	non patterns	flow patterns using	covered fish species		
benefit covered fish	now patterns		operable barriers	covered non species		
species			operable burriers			
F5. Spatial	Low-fewest	Low-	Low-	High – greatest		
flexibility for	opportunities	opportunities for	opportunities for	opportunities for		
restoring additional	among Options for	restoration in the	restoration in the	restoration		
physical habitat for	restoration (~28% of	north and central	north and central	throughout the		
covered fish species	planning area	Delta (~35% of	Delta (~35% of	Delta (~75% of		
covered fish species	available); Suisun	planning area	planning area	planning area		
	Marsh included in	available)	available)	available)		
	Option 1 and all	avaliablej	avallable)	avaliable		
	other Options					
Criterion #14. Relat	tive degree of reversib	ility of the Ontion one	a implemented			
F6. Relative	High – greatest	Moderate — loss of		Low – substantial		
	0		Very Low –	loss of investment		
practicability to	ability to reverse	capital investment	substantial loss of			
reverse the Option	because no costs	associated with	investment	associated with		
	associated with	abandonment or	associated with	abandonment or		
	removal of	removal of new	abandonment or	removal of a		
	infrastructure	infrastructure	removal of a	peripheral aqueduct		
	relative to current		peripheral aqueduct	and other new		
	conditions		and other new	infrastructure;		
			infrastructure;	politically difficult		
			politically difficult	to reverse		
N. c			to reverse			
Notes: 1. See Table 2-6 for ex	planations of tools and scales us	ed to score high, moderate, low,	and very low for each metric			

7.3.1.1 Criterion #11. Relative degree to which the Option will be able to withstand the effects of climate change (e.g., sea level rise, changes in runoff), variable hydrology, seismic events, subsidence of Delta islands, and other large-scale changes to the Delta

Criterion #11 addresses the ability of the Options to withstand predicted possible large-scale changes to the Delta. The evaluation of this criterion was based on a qualitative assessment of the durability of each Option to withstand the effects of catastrophic events, such as earthquake or flood and climate change-caused sea level rise, on habitat restoration and water supply conveyance. Options 3 and 4 afford the greatest protection from catastrophic disruption of water supply and Option 4 the greatest protection from loss of restored habitat. Option 1 offers the least protection from catastrophic events and sea level rise. Option 2 falls between Options 1 and Options 3 and 4 in avoiding these risks.

Option 1 is expected to be at the greatest risk of water supply disruption from catastrophic levee failures that could result from seismic and flood events because Option 1 does not include improvements to protect conveyance facilities (Table 7-14). Option 1 would support the least durable habitat restoration sites because a smaller area (approximately 28% of the planning area) is available for locating these sites. Greater clustering of restoration sites results in more vulnerability to larger losses of habitat with localized levee failures. In addition, habitat restoration under Option 1 is less likely to be located at sites that could be adapted to address sea level rise because there are fewer locations from which to choose. All Options, however, include restoration outside the planning area at Suisun Marsh, an area that likely is less subject to habitat loss from seismic or flood events than much of the planning area.

Option 2 affords a better level of protection of water supply from catastrophic events, but is still at a higher risk than Options 3 and 4 because the levees that direct conveyance through the north Delta are at greater risk of failure from seismic and flood events than the peripheral aqueduct included in Options 3 and 4 (the aqueduct would be expected to be engineered to withstand probable seismic and flood events). Option 2 provides more area (approximately 35% of the planning area) than Option 1 to distribute restoration sites more broadly to avoid large losses from localized levee failures. Because Option 2 provides more area for habitat restoration than Option 1 it provides more flexibility to locate restoration sites in areas suitable to withstand sea level rise.

Option 3 would provide more protection to water supply from seismic and flood events than Options 1 and 2 because the peripheral aqueduct component of Option 3 is more durable in a seismic or flood event than through-Delta conveyance. Option 3 offers redundancy in the protection of water supply delivery through its dual system and each conveyance offers a back-up to the other should one fail. Option 3 is the only Option with this feature. Option 3 provides more area (approximately 35% of the planning area) than Option 1 to distribute restoration sites more broadly to avoid large losses from localized levee failures. Because Option 3 provides more area for habitat restoration than Option 1 it provides more flexibility to locate restoration sites in areas suitable to withstand sea level rise. Option 3 is comparable to Option 2 in the protection of restoration sites and less protective of restoration sites than Option 4.

Option 4 would provide more protection to water supply facilities from seismic or flood events than Options 1 and 2 because the peripheral aqueduct component is expected to be more

durable than in-Delta levees. Option 4 does not have the conveyance redundancy that provides

- a back-up system for water supply that is part of Option 3. Relocating the intake to the vicinity
- of Hood reduces the potential for sea level rise to affect water quality. Option 4 provides
- 3 substantially more area (approximately 75% of the planning area) than all other Options for
- 4 habitat restoration and, therefore, the most flexibility to find sites suitable to address sea level
- 5 rise and to better distribute sites to avoid large habitat losses from localized levee failures.
- 7.3.1.2 Criterion #12. Relative degree to which the Option could improve ecosystem processes that support the long term needs of each of the covered species and their habitats with minimal future input of resources.
- 9 This criterion addresses the performance of each Option with regard to avoiding the need for
- 10 future on-going input of resources to support the conservation of covered species. The
- 11 evaluation determined that Option 4 would rank highest in sustainability and avoiding such
- 12 costs. Option 3 ranked second and Options 1 and 2 lowest because of on-going costs of in-Delta
- 13 facilities operations and fish salvage to achieve conservation objectives (Table 7-14).
- Options 1 and 2 would entail ongoing management actions (i.e., salvage and hauling) and costs
- 15 to address entrainment of covered fish species at the SWP/CVP export facilities and provide
- 16 limited flexibility for adaptively managing Delta flows to meet species needs in the future. Use
- of the Delta for both fish habitat and through-Delta conveyance often results in competing
- operational priorities. Options 1 and 2 are wholly dependent on through-Delta conveyance and
- 19 therefore are more likely to incur the costs associated with export restrictions. Option 2 requires
- 20 the on-going cost of barrier management and monitoring to maintain the conservation benefits
- 21 the barriers provide for fish.
- Option 3 would be more likely to sustain ecosystem processes into the future than Options 1
- 23 and 2. This Option's dual conveyance facilities provide opportunities to adjust the timing of
- 24 through-Delta pumping to minimize the likelihood for fish entrainment and its associated
- 25 salvage costs. Use of the Delta for both fish habitat and through-Delta conveyance often results
- 26 in competing operational priorities. Option 3, therefore, is considered less likely than Option 4
- 27 to sustain ecosystem processes with minimal future inputs because of ongoing costs that would
- 28 be associated with barrier management and monitoring.
- 29 Option 3 also may require ongoing management actions depending on operational rules and
- 30 changes in fish status as a result of overall conservation actions.
- 31 Option 4 provides the greatest habitat sustainability with the lowest future input of resources of
- 32 the Options because it allows for the largest area of the Delta to be used for physical and
- 33 hydrological habitat restoration (Table 7-14). Natural processes could be allowed to support fish
- 34 habitat, as opposed to more engineered solutions required under Options that must balance
- 35 within-Delta operations between habitat and water supply conveyance. Habitat management
- 36 under Option 4 is expected to require less input of funds and other resources to sustain fish
- 37 populations. In addition, the much reduced level of entrainment under Option 4 would avoid
- 38 the need for funding ongoing fish salvage at CVP and SWP intake facilities or to incur the costs
- 39 associated with export restrictions.

7.3.1.3 Criterion #13. Relative degree to which the Option can be adapted to address needs of covered fish species over time

- 3 Criterion #13 addresses the ability to which the Options can be adapted to address the potential
- 4 future needs of the covered fish species. The evaluation of this criterion was based on a
- 5 qualitative assessment of the likely flexibility under each Option to adaptively manage Delta
- 6 flows and restore additional habitat areas to address current uncertainties and future needs of
- 7 the covered fish species. Option 4 is the most flexible in allowing for adaptive management of
- 8 both hydrologic patterns and location of habitat restoration in the Delta. Options 2 and 3 are
- 9 ranked second because of constraints on adaptive management. Option 1 ranked last with the
- 10 most limited flexibility.

1

2

34

- Option 1 is considered to be the least adaptable of the Options because, to meet water supply
- objectives, opportunities to adaptively manage Delta flow patterns are minimal. This Option
- lacks the flexibility for restoring habitats in the central, south, and east Delta if needed to meet
- 14 the future needs of covered fish species. Under Option 1, only about 28% of the Delta is
- 15 available for restoration of natural hydrology.
- 16 Option 3 is more constrained than Option 4, but does provide opportunities to adaptively
- 17 manage Delta flows, having the ability to opportunistically convey water through-Delta or via a
- 18 peripheral aqueduct to maximize benefits for covered species. The operable barriers along
- 19 Middle River under Option 3 and 2 limit the opportunities for managing Delta flows to a much
- smaller proportion of the Delta than under Option 4. Under Options 2 only about 35% of the
- 21 Delta is available for restoration of natural hydrology. With the opportunity to use the
- 22 peripheral aqueduct, Option 3 would have greater flexibility than Option 2 in the operation of
- the in-Delta barriers to manage hydrologic conditions east of Middle River for the benefit of
- 24 covered fish species and other aquatic organisms. The extent of areas available for habitat
- 25 restoration and adaptive management is more limited under Option 3 than under Option 4.
- 26 Option 4 is expected to provide the greatest flexibility among the Options to adaptively manage
- 27 Delta flows and restored physical habitat for the benefit of covered fish species (Table 7-14).
- 28 Because it is not constrained by the need to maintain the export quality of water in a through-
- 29 Delta conveyance, Option 4 provides for the greatest geographic extent and percentage of the
- 30 Delta area available for habitat restoration should it be necessary to increase the extent of or
- 31 redistribute restored habitat for covered species in the future. Under Option 4, approximately
- 32 75% of the Delta would be available for restoration of natural hydrology and therefore would
- provide the best locations for physical habitat restoration.

7.3.1.4 Criterion #14. Relative degree of reversibility of the Option once implemented

- 35 Criterion #14 addresses the relative ability to reverse each of the Options once they are
- 36 implemented. The evaluation of this criterion was based on a qualitative assessment of the
- 37 practicability for reversing the Options based on likely levels of engineering feasibility, public
- acceptance, and costs for doing so. Option 1 is expected to be the most reversible based on the
- 39 assumption of limited new facilities (Table 7-14). Option 2 would be more reversible than
- 40 Options 3 and 4 because it does not involve the peripheral aqueduct. Option 4 ranked third
- because of greater limits on reversing a completed peripheral aqueduct. Option 3 ranked last
- because it includes the largest amount of initial capital investment.

- Option 1 is considered to be the most easily reversed of the Options because no costs associated
- 2 with the removal of infrastructure would be incurred relative to current conditions.
- 3 Option 2 is less reversible than Option 1, but is considered to be substantially more reversible
- 4 than Options 3 and 4, which would entail removal or abandonment of a peripheral aqueduct at
- 5 likely enormous cost and loss of capital investment. Likely costs associated with reversing
- 6 Option 3, which would also include removal or abandonment of Delta barriers, would be
- 7 somewhat higher than Option 4. Because costs associated with reversing Options 3 and 4 and
- 8 the consequent loss of capital investment would be substantial, the probability for obtaining the
- 9 level of public acceptance necessary to reverse these Options is considered low.

7.4 COMPARISON OF THE OPTIONS RELATIVE TO OTHER RESOURCE IMPACTS CRITERIA

12 This section provides a comparison of the performance of each Option relative to each of the

- criteria for impacts on other resources. The summary provided here is based on the evaluations
- presented in Sections 3.3, 4.3, 5.3, and 6.3. Table 7-15 presents a summary description of the
- performance of each Option relative to the evaluation metrics provided in Section 2. Table 7-2
- 16 provides a summary comparison of the performance of each Option relative to each of the
- 17 criteria.

1011

18

Table 7-15. Comparison of the Performance of the Options Relative to Other Resource Criteria Metrics¹

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4
		ption avoids impacts	on the distribution a	and abundance of
O1. Ability to avoid	ve species in the BDO High—no impacts	Low—impacts on	Very Low – may	Very Low – may
temporary and	would occur	terrestrial habitats	incur substantial	incur substantial
permanent impacts on	because no new	from levee	impacts on	impacts on
terrestrial habitat in the planning area	facilities would be constructed	improvements could be between 500-1,000 acres.	terrestrial habitats associated with construction of a peripheral aqueduct (likely over 1,000 acres)	terrestrial habitats associated with construction of a peripheral aqueduct (likely over 1,000 acres)
O2. Ability to avoid entrainment of other native aquatic species at SWP/CVP pumps under the Option	Low – Ongoing entrainment of aquatic organisms in south Delta	Low – Ongoing entrainment of aquatic organisms in south and central Delta; possible adverse effects of barriers to fish movement	Moderate — Reduction in entrainment of aquatic organisms in south Delta and minimal entrainment anticipated at intake of peripheral aqueduct; possible adverse effects of barriers to fish	High – No entrainment of aquatic organisms in south Delta and minimal entrainment anticipated at intake of peripheral aqueduct
			barriers to fish movement	

Table 7-15. Comparison of the Performance of the Options Relative to Other Resource Criteria Metrics¹ (continued)

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4
Criterion #16. Relative of	legree to which the O	ption avoids impacts	on the human enviro	onment.
O3. Ability to avoid disruption of transportation/traffic patterns	High – facilities would not be constructed, therefore, infrastructure would not be affected	Moderate – Levee improvement work could affect rail line, Highway 4 and county roads	Low – construction of a peripheral aqueduct would affect a substantial number of roads and rail lines	Low – construction of a peripheral aqueduct would affect a substantial number of roads and rail lines
O4. Ability to avoid removal of agricultural land for construction of new facilities	High – facilities would not be constructed, therefore, agricultural lands would not be affected	Moderate — Improvements to about 34 miles of levees could result in removal of agricultural land from production	Very Low — construction of a peripheral aqueduct would likely remove a substantial amount of land from production	Very Low — construction of a peripheral aqueduct would likely remove a substantial amount of land from production
O5. Ability to avoid reductions in irrigation water quality for agriculture in the Delta	High — unlikely to change in-Delta water quality conditions relative to existing conditions	Moderate — potential to lower water quality west of Middle R. barriers during growing season, but increase in water quality east of the Middle River barriers	Moderate — potential to lower water quality west of Middle R. barriers during growing season, but increase in water quality east of the Middle River barriers	Moderate — potential to lower water quality in the south and central Delta during the growing season
O6. Ability to provide high quality export water for use in service areas	Very Low—quality of exported water is expected to be similar to current conditions	Low — quality of exported water is expected to be improved relative to current conditions	Moderate — quality of exported water is expected to be improved relative to current conditions and better than Option 2	High—quality of exported water would be substantially better than current conditions and among the Options
O7. Ability to avoid impacts on other, non-biological CEQA/NEPA resources (e.g., cultural resources, air quality, noise, environmental justice)	High — facilities would not be constructed, therefore, unlikely to affect other resources relative to existing conditions	Low—large construction footprint from levee improvements, but mitigation costs relatively low	Very Low— relatively large construction footprint increases potential for substantial impacts and high mitigation costs	Very Low— relatively large construction footprint increases potential for substantial impacts and high mitigation costs

Table 7-15. Comparison of the Performance of the Options Relative to Other Resource Criteria Metrics¹ (continued)

Metric	Option 1	Option 2 (with pump)	Option 3	Option 4
	egree of risk of the Op e BDCP Planning Area	U .	on sensitive species ar	nd habitats in
O8. Ability to provide Delta outflows beneficial to species in Suisun Marsh and Bay	Moderate – provides Delta outflows (15,000 cfs) similar to base conditions (15,000 cfs)	Moderate – similar Delta outflows to base conditions	High—increases Delta outflows (20,000 cfs) from base conditions (15,000 cfs)	High—increases Delta outflows (21,000 cfs) from base conditions (15,000 cfs)
O9. Provides potential for Sacramento, American, and Feather River water temperatures beneficial to native fish species, measured by end-of-September Shasta, Folsom, and Oroville Reservoir storage volumes	Moderate — improves storage volumes during critical water years relative to current conditions	Moderate — improves storage volumes during critical water years relative to current conditions	High—improves storage volumes during critical water years relative to current conditions and Options 1, 2, and 4	Low – might affect storage volumes during dry and critical water years relative to current conditions and the other Options

7.4.1.1 Criterion #15: Relative degree to which the Option avoids impacts on the distribution and abundance of other native species in the BDCP Planning Area

- 5 Criterion #15 addresses the degree to which each of the Options avoids potential impacts on
- 6 native species (other than the covered species) in the planning area. The evaluation of this
- 7 criterion was based on a qualitative assessment of the likely degree of impacts on native aquatic
- 8 organisms and terrestrial species present in the Delta. Option 1 would have the least impact on
- 9 terrestrial species but potentially the greatest impact on aquatic species. Ranked second, Option
- 4 avoids much of the impacts on aquatic species but has large effects on terrestrial species.
- Option 2 was ranked third because it has the largest effects on aquatic species and substantial
- effects on terrestrial species from levee construction. Ranked lowest, Option 3 impacts aquatic
- species and has large effects on terrestrial species.
- 14 Without new facilities, Option 1 would have no construction impacts on native terrestrial
- 15 species, but on-going entrainment of native aquatic species at the pump facilities would
- 16 continue. Option 1 would be expected to have greater entrainment of aquatic organisms than
- 17 the other Options because of the location and more exposed condition of the pump facilities.
- 18 Option 2 would have minor impacts on terrestrial and aquatic species associated with
- 19 construction of operable barriers and the siphon, but 34 miles of levee improvements could
- 20 result in substantial impacts on riparian and terrestrial species on islands surrounding Middle
- 21 River and Victoria Canal. Option 2 would have a higher probability for entraining aquatic
- 22 organisms from the south Delta than Options 3 or 4 because south Delta exports under Option 3

1 2

- would be much reduced and exports would not be taken from the south Delta under Option 4.
- 2 The placement and operation of the barriers along Middle River under Options 2 could result in
- 3 impacts on native aquatic organisms if the barriers sufficiently impede the movement of aquatic
- 4 species to and from the east and central Delta. Because the barriers are expected to be operable,
- 5 there is the opportunity to adjust operation of barriers to minimize these potential impacts.
- 6 Overall, Option 3 is anticipated to have the largest impacts on native species in the planning
- 7 area as a result of the large construction impacts of the peripheral aqueduct and additional
- 8 impact of the barriers and siphon (Table 7-15). Options 3 would result in substantial impacts on
- 9 terrestrial native species due to construction of a peripheral aqueduct across over 40 miles of
- 10 upland, riparian, and wetland habitats. The placement and operation of the barriers along
- 11 Middle River under Options 3 could result in impacts on native aquatic organisms if the
- barriers sufficiently impede the movement of aquatic species to and from the east and central
- Delta. Because the barriers are expected to be operable, there is the opportunity to adjust
- operation of barriers to minimize these potential impacts.
- 15 Options 4 would result in substantial impacts on terrestrial native species due to construction of
- a peripheral aqueduct across over 40 miles of upland, riparian, and wetland habitats. Option 4
- is expected to have the least impacts on native aquatic organisms. Water would not be exported
- 18 from the south Delta, thereby eliminating the probability of entrainment at the SWP/CVP
- 19 pumping facilities. Operation of a state-of-the-art fish screen at the intake of the peripheral
- 20 aqueduct is expected to minimize entrainment of aquatic organisms. The loss of food from the
- 21 Sacramento River may result in greater impacts on aquatic food supply in the Delta than under
- 22 Options 1 and 2.

7.4.1.2 Criterion #16. Relative degree to which the Option avoids impacts on the human environment.

- 25 Criterion #16 addresses the relative degree to which implementation of each Option could
- 26 impact the human environment. The evaluation of this criterion was based on a qualitative
- 27 assessment of likely impacts on NEPA/CEQA resource categories. The evaluation of Criterion
- 28 #16 focuses on the likely range of adverse direct and indirect impacts of the Options in the
- 29 planning area and not the indirect impacts to water quality and water supply reliability and in
- 30 the service areas. These issues in the service areas are addressed in Criteria #8 and #11. Option
- 31 1 is expected to have the least adverse effects on the human environment with limited new
- 32 construction. Option 2 was ranked second with more moderate construction impact due to the
- extent and location of new facilities. Option 4 ranked third and Option 3 last with the large
- 34 amount of construction impacts associated with new facilities.
- 35 Option 1 would have the least overall impacts on the human environment because it would not
- 36 entail any construction that could disrupt use of the Delta or degrade the human environment
- 37 and water quality conditions for agriculture in the Delta would be similar to existing conditions
- 38 (Table 7-15). Although Option 1 would have the fewest direct impacts, it is expected to result in
- 39 the lowest export water quality with consequent adverse effects on treatment costs, agricultural
- 40 production, and human health. Option 1 is also the most vulnerable among the Options to
- 41 future disruption of water supply to service areas as a result of catastrophic events.

- Option 2 is expected to have fewer impacts than Options 3 and 4 because improvements of
- 2 levees under Option 2 is anticipated to affect fewer resources and with less magnitude of impact
- 3 than the peripheral aqueduct construction. Option 2, is expected to provide higher water
- 4 quality and be less vulnerable to supply disruption than Option 1, but portions of the
- 5 conveyance system would still be vulnerable to future disruption and loss of water supply to
- 6 service areas.

- 7 Options 3 and 4 entail construction of a peripheral aqueduct which could lead to substantial
- 8 permanent (e.g., removal of agricultural land from production; changes in land use) and
- 9 temporary (e.g., noise, traffic, air quality) impacts. Because Option 3 includes construction of
- dual conveyance facilities, it would result in greater overall impacts on the human environment
- than the other Options. Options 3 and 4 are expected to be substantially less vulnerable than
- 12 Options 1 and 2 to future disruption of water supply. Export water quality improvements
- 13 would be successively greater and attendant impacts on treatment costs, agricultural
- production, and human health successively reduced under Options 2, 3, and 4 in that order.

7.4.1.3 Criterion #17. Relative degree of risk of the Option causing impacts on sensitive species and habitats in areas outside of the BDCP planning area.

- 17 Other Resource Impacts Criterion #17 addresses the degree of risk for causing impacts on other
- sensitive species and habitats outside of the planning area. The evaluation of this criterion was
- 19 based on hydrodynamic modeling results for Delta outflows and end-of-September reservoir
- 20 storage volumes as indicators of how each of the Options may affect species and habitats
- 21 downstream and upstream of the Delta, respectively. Option 3 ranked highest because it is
- 22 most flexible in supporting both upstream and downstream operations beneficial to biological
- 23 resources (Table 7-15). Option 4 ranked second because of its ability to support greater Delta
- outflows than Options 1 and 2. Options 1 and 2 were considered similar in their effects on
- 25 species outside the planning area.
- 26 Options 1 and 2 are expected to have a neutral effect relative to base conditions on species and
- 27 habitats downstream of the Delta because outflows provided under Options 1 and 2 are
- 28 expected to be similar to base conditions.
- 29 Options 3 and 4 would provide average annual Delta outflows higher than Options 1 and 2 and
- 30 base conditions. Delta outflows during critical months of March and April in critical dry years
- 31 are similar across all Options. Because they generally would provide for greater Delta outflows,
- 32 Option 3 and 4 would be the less likely to impact species and habitats in Suisun Marsh and Bay
- and other downstream locations.
- 34 In most water year types, the capacity for providing cold water releases from Shasta, Folsom,
- 35 and Oroville Reservoirs would be similar under each of the Options and to current conditions.
- 36 Reservoir storage volumes under Option 4 may be less than under the other Options in dry and
- 37 critical water years and therefore may be the least likely to provide for cold water releases in
- 38 those years (Table 7-15). If selected, operations under Option 4 would need to be refined so that
- 39 cold water temperature requirements are met.

1 7.5 CONCLUSIONS - OVERALL COMPARISON OF THE OPTIONS

2 7.5.1 Biological Criteria

- 3 The comparison of overall biological benefits of the Options focused primarily on the estuarine
- 4 species that are most dependent on the Delta (delta smelt, longfin smelt, and splittail). These
- 5 species are at greater population-level vulnerability to in-Delta impacts than salmon, steelhead,
- 6 and sturgeon.
- 7 Option 4 would provide the greatest benefits among all Options to the estuarine species most
- 8 dependent on the Delta (Table 7-3). Option 4 would provide the most opportunity to address
- 9 important stressors to delta smelt, longfin smelt, and splittail. Option 4 also would perform
- well for salmonids relative to other Options.
- Option 3 would provide the next greatest benefits to the most vulnerable estuarine fish and also
- 12 would perform well for salmonids.
- Option 2 would not perform as well as Options 4 for any species; it would provide comparable
- benefit to salmonids and sturgeon as Option 3, but provides lower benefit to the more
- vulnerable estuarine species. Option 2 would outperform or match Option 1 for all species.
- Option 1 performs the poorest for covered fish species. Option 1 would be outperformed by all
- other Options for delta smelt, longfin smelt, San Joaquin River salmonids and white sturgeon.
- Option 1 is matched in performance by all other Options for Sacramento River salmonids, green
- 19 sturgeon, and splittail.

20 7.5.2 Planning Criteria

- 21 Options 3 and 4 both address planning criteria well and rank higher than Options 1 and 2 in all
- cases (Table 7-3). Option 4 may be slightly more cost effective and practicable than Option 3,
- but Option 3 provides greater flexibility to meet water supply goals. Overall Options 3 and 4
- 24 were tied for first rank.
- 25 Options 1 and 2 were both considered poor in meeting planning criteria. Option 1 was
- 26 considered too limiting to meet dual habitat conservation and water supply goals and too
- 27 expensive in the long term due to large on-going costs of low export water quality. Option 2
- 28 includes a number of technical challenges for both conservation and water supply objectives.
- 29 Option 2 costs are relatively high because of levee construction, more limited improvement in
- 30 export water quality, and additional high cost facilities likely to be necessary (e.g., pump facility
- 31 and fish screens).

32 7.5.3 Flexibility/Durability/Sustainability Criteria

- Option 4 has the most flexibility and adaptability to adjust conservation approaches both for
- 34 physical habitat restoration and flow management with the least input of future resources
- 35 (Table 7-3). Options 3 and 4 both rank highest for durability in the face of sea level rise and
- 36 catastrophic seismic and flood events. Options 3 and 4 are the least reversible as they involve
- 37 the most input of resources. Overall Option 4 was ranked highest for flexibility, durability and

7.0 Comparison of the Options Relative to Biological Criteria September 17, 2007

- sustainability. Option 3 ranked second because of its more limited adaptability due to smaller
- 2 area available for restoration of natural hydrology and physical habitat restoration for covered
- 3 fish species.
- 4 Option 2 is less durable than Options 3 and 4 and more durable than Option 1 in the face of
- 5 catastrophic events and sea level rise. Option 2 is less flexible than Option 3 and much less
- 6 flexible than Option 4 to conduct adaptive management to address the needs of covered fish
- 7 species and with a minimum input of future resources.
- 8 Option 1 was ranked the lowest because of it high risk to loss of habitat and water supply from
- 9 catastrophic events and sea level rise. While Option 1 is obviously the most reversible, it has
- the least flexibility to adapt water operations and physical habitat restoration to meet the future
- 11 needs of species without substantial input of resources.

12 7.5.4 Other Resource Impacts Criteria

- 13 Option 1 ranked highest for avoiding direct impacts on other biological and human resources
- because of the minimal amount of new infrastructure required (Table 7-3). The high indirect
- 15 effects of Option 1 in service areas were not addressed in this category, but were addressed in
- the planning criteria under costs. If indirect effects on the human environment of Options 1 in
- 17 water service areas over the long-term were included in the evaluation of other resource
- impacts criteria grouping rather than in the planning criteria, then Option 1 may have been
- 19 ranked lowest for other resource impacts.
- 20 Option 2, with a smaller construction impact footprint than Options 3 or 4, ranked second in
- 21 avoiding impacts. Impacts on biological resources both inside and outside the Delta would be
- 22 higher than Option 4.
- 23 Option 4 ranked third in avoiding impacts. It was ranked behind Option 2 because of the
- 24 greater direct impacts human environment and ahead of Option 3 because it does not include
- 25 the new in-Delta facilities of Option 3.
- 26 Option 3 ranked last as it would involve the most new construction and would have the most
- 27 direct impacts on biological resources and the human environment in the Delta. Options 3 and
- 4 allowed for the most Delta Outflow and would be expected to benefit aquatic species in
- 29 Suisun Marsh and Bay.

30 7.5.5 Overall Conclusions

- 31 Each Option offers opportunities and constraints to meeting conservation and water supply
- 32 goals. The conclusions presented in this evaluation regarding which Option would be most
- 33 successful in meeting the various criteria are dependent on many assumptions used in the
- 34 analysis, reflecting the uncertainties in the current state of knowledge. Drawing more general
- 35 conclusions about how each option performs across all of the criteria compounds these
- 36 assumptions and their uncertainties. Thus, hard and fast conclusions about the overall
- 37 performance of any particular option should be approached cautiously.

- With the above caveats in mind, the conclusion of this report is that both Options 3 and 4
- 2 appear to provide significant improvements over the first two options across the biological,
- 3 planning and flexibility criteria, and both, in turn, score less well in the "other resource
- 4 impacts" category.
- 5 Options 1, 2, and 3 all geographically split the Delta in some way to accommodate the dual use
- 6 for water conveyance and species conservation. Option 1 focuses physical habitat restoration in
- 7 the north and west Delta to avoid the conflict at sites in the central and south Delta between
- 8 conveyance hydrology and the restoration of natural hydrology. Options 2 and 3 split the Delta
- 9 through engineered structures to separate conveyance to the east and habitat conservation to
- 10 the west. In doing so, Options 2 and 3 fall in between the extent of habitat opportunities
- provided by Option 1 (the lowest) and Option 4 (the highest).
- Option 3 appears to perform better than all other options in its ability to meet water supply
- planning goals and objectives, and in its resiliency in response to catastrophic events. Its
- 14 performance biologically is consistently superior to Options 1 and 2, but is less robust than
- Option 4. Its dual conveyance feature may provide significant operational flexibility over and
- 16 above the other options.
- Option 4 appears to provide the greatest opportunity to meet the greatest number of criteria. It
- allows for the most opportunities over a much larger proportion of the Delta to combine the
- 19 restoration of natural hydrology beneficial to covered fish species with the restoration of
- 20 physical habitat for those species. It separates geographically and hydrologically the frequently
- 21 conflicting requirements (structural and operational) of export water conveyance and aquatic
- 22 species conservation (allowing for the greatest flexibility in accomplishing habitat
- conservation). Finally, it provides high long-term water supply reliability with the highest export water quality at the lowest overall cost. A key constraint of Option 4 is the limitation of
- 25 export capabilities to a single north Delta intake a limitation which affects both water supply
- 26 reliability and Delta inflows for conservation.
- 27 In summary, this evaluation describes how each of the Options performs in relation to a wide
- 28 range of criteria. This information will assist the Steering Committee over the course of the fall
- 29 in selecting an option to carry forward into the planning process. The Steering Committee may
- 30 select of the four options as is, or it may further refine an option into a new hybrid to take into
- 31 the planning process.

